



# Alltesta™ Automated Analyzer

## Technical Specifications

## Technical Specifications

Parameters	Alltesta™ Isocratic Automated Analyzer	Alltesta™ Gradient Automated Analyzer
Autosampler type	Random access	Random access
Sample capacity	Automatic, 48/96 Vials	Automatic, 48/96 Vials
Injection type	High pressure	High pressure
Injection Range	1-75 µL	1-75 µL
Injection volume accuracy	±1 µL	±1 µL
Pump operation	Isocratic	Isocratic, Gradient
Pump type	Syringe	Syringe, Gradient
Flow Rate Range	0.001 to 8.0 mL/min	0.001 to 8.0 mL/min
Flow rate accuracy	1% of full-scale	1% of full-scale
Pressure limit	up to 3000 psi (206 bar)	up to 3000 psi (206 bar)
Pressure precision measurement	±1 psi (0.07 bar)	±1 psi (0.07 bar)
Detector noise Level	< 0.05 mAU	< 0.05 mAU
Detection sample rate	20Hz	20Hz
Detector wavelengths, standard	275, 470, 520, 630 nm	275, 470, 520, 630 nm
Detector wavelengths, custom	Any 4 starting from 255 nm	Any 4 starting from 255 nm
Supported columns	Any	Any
Column Length	Any	Any
Connectivity	Wi-Fi, Ethernet land line, Mobile cell network	Wi-Fi, Ethernet land line, Mobile cell network
Power Supply	100-240V, 50-60Hz	100-240V, 50-60Hz
Liquid connection type	10-32 UNF compression type	10-32 UNF compression type

<b>Parameters</b>	<b>Alltesta™ Isocratic Automated Analyzer</b>	<b>Alltesta™ Gradient Automated Analyzer</b>
Materials in contact with liquid	SS316, PTFE, PEEK, UHMW PE, EPDM, Glass, 17-4 SS diamond coated	SS316, PTFE, PEEK, UHMW PE, EPDM, Glass, 17-4 SS diamond coated
Operating Temperature	0 to 40° C, non-condensing	0 to 40° C, non-condensing